

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
WO 2004/001435 A1

(51) International Patent Classification<sup>7</sup>: G01R 33/36

(21) International Application Number:  
PCT/IB2003/002386

(22) International Filing Date: 11 June 2003 (11.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02077474.1 21 June 2002 (21.06.2002) EP

(71) Applicant (for all designated States except US): KONIN-  
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VAN DEN BRINK,  
Johan, S. [NL/NL]; C/o Prof. Holstlaan 6, NL-5656 AA  
Eindhoven (NL).

(74) Agent: WOLFS, Marc, J., M.; Philips Intellectual Prop-  
erty & Standards, Prof. Holstlaan 6, NL-5656 Eindhoven  
(NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,  
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,  
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: MAGNETIC RESONANCE IMAGING APPARATUS AND METHOD

(57) Abstract: The present invention relates to a magnetic resonance imaging apparatus comprising an RF coil system comprising M RF coils (11-18) for detecting RF signals from a region of interest, M being an integer larger than 2, and N receiver channels (C1-C4) for receiving and processing the detected RF signals, N being an integer larger than 1 and smaller than M. According to the invention at least two RF coils (12, 16; 14, 18) are combined for reception of RF signals of said RF coils with a single receiver channel, wherein said at least two RF coils are selected so as to provide maximum spatially varying coil sensitivities along the principal axis for coil sensitivity encoding. The proposed MRI apparatus provides an optimal solution enabling it to be used with the SENSE method. The general idea is to have as much individuality as possible along the preferred or actual sense reduction direction and to feature as much spatial distinctness as possible along the axes of primary clinical interest.

WO 2004/001435 A1